

Coating smoothing
made from natural lime
for indoors and outdoors



SMARTOPRET® CACHET BLEU



INTERIOR AND
EXTERIOR WALLS



STAINLESS STEEL
TROWEL



MECHANICAL MIXING



DILUTE WITH WATER



DESCRIPTION

SMARTOPRET CACHET BLEU is a lime-based powder smoothing filler natural and selected binders.

SMARTOPRET CACHET BLEU can be applied indoors and outdoors , on horizontal surfaces (ceilings) and on vertical surfaces (walls, posts and partitions).

USE

SMARTOPRET CACHET BLEU is used as a finishing coat for smoothing walls and trimmed ceilings, inside and outside, a single coat of 1 mm maximum provides a smooth finish ready to paint.

SMARTOPRET CACHET BLEU is very easy to apply with good adhesion to treated surfaces, easy to sand, and can be covered with all types of paint.

APPLICATION

The product application steps are like that:

- 1 - Dilute the 20 kg bag of **SMARTOPRET CACHET BLEU** in 7 (seven) liters of clean water.
- 2 - Mix using a mechanical stirrer for a maximum of 3 minutes (on slow speed) , until a lump-free batter forms.
- 3 - Leave to stand for 15 minutes before application.
- 4 - Apply the smoothing coating after the final drying of the covered support
- 5 - Spread the coating using a stainless steel trowel in one layer until you obtain the desired thickness on average 1 millimeter.

SMARTOPRET CACHET BLEU can be applied with a trowel , blade or by a metal trowel.

- The treated surfaces can remain raw or covered by all types of paintings.
- The treated surfaces can remain raw or covered with paint or with the **SMARTOPRET CACHET BLEU** coating for a smooth finish.

COMPOSITION

SMARTOPERET CACHET BLEU is composed of:

- Natural lime,
- Mineral fillers, and
- Various additives.

CONDITION STORAGE

SMARTOPRET CACHET BLEU is available in a paper bag designed according to packaging standards to protect the product against any contact likely to alter the desired quality. Each bag contains 20 Kg of powder. The product remains valid for 36 months from the date of manufacture. It must be kept in its original packaging (unopened) away from humidity and without direct contact with the ground.

RECOMMENDATIONS PRECAUTIONS OF EMPLOYMENT

SMARTOPRET CACHET BLEU should be used without adding any other product

- It is recommended to ventilate the rooms after application to facilitate the drying of the surfaces.
- The fresh plaster must be protected from frost and from means of drying too quickly.
- Paints and coatings should be applied after curing complete with coating.
- It is advisable to use gloves and protective goggles.
- In case of contact with eyes, rinse with water and consult your doctor.

FEATURES TECHNIQUES

| | |
|-------------------------------|---|
| Granulometry | 15 microns |
| Volumic mass | Abo 860 (kg/m ³) |
| Mixing water | 25 at 30% |
| Maximum application thickness | 1 at 2 mm |
| Yield | 0,4 kg/1m ² /mm |
| Drying time | 40 à 60 min at a temperature (5°C - 35°C) |
| Working temperature | Between 5°C et 35°C |
| Recovery time | 20 at 24 hours |
| Reaction to fire | Classe A1: incombustible |

This document is provided for information only, our company reserves the right to modify the information contained in it at any time.